

Detailed technical parameters JCL Ceramic Discharge Metal Halide Lamp JENBO

Reference	Rated W	V	A	K	(Lm)	(Lm/W)	Life (Hrs)	Base	Diameters (mm)	Operating position			
JCL ST 150 HR	150	90	1,6	3000K	15000	100	6600	GZY9.5	22 x 110	any			
JCL ST 150/2 HR	150	90	1,6	4000K	14000	93	6600	GZY9.5	22 x 110	any			
JCL ST 250 HR	250	95	2,6	3200K	25000	100	4000	GZY9.5	22 x 110	any			
JCL ST 250/2 HR	250	95	2,6	3800K	23000	92	4000	GZY9.5	22 x 110	any			
JCL ST 500 HR	500	95	5,2	3200K	40000	80	1000	GY22	38 x 175	any			

Reference	Rated W	V	A	K	(Lm)	(Lm/W)	CRI (Ra)	Life (Hrs)	Base	Diameters (mm)	Operating position		
JCL-T 35W/830	37	88	0,42	3000K	3300	89	>79	>9000	G12	19 x 100	any		
JCL-T 35W/942	37	88	0,42	4200K	3300	89	>88	>9000	G12	19 x 100	any		
JCL-T 70W/830	72	88	0,82	3000K	6600	92	>82	>9000	G12	19 x 100	any		
JCL-T 70W/942	72	88	0,82	4200K	6600	92	>90	>9000	G12	19 x 100	any		
JCL-T 150W/830	145	96	1,51	3000K	14000	97	>83	>9000	G12	19 x 100	any		
JCL-T 150W/942	145	90	1,61	4200K	12700	88	>84	>9000	G12	19 x 100	any		

Reference	Rated W	V	A	K	(Lm)	(Lm/W)	CRI (Ra)	Life (Hrs)	Base	Diameters (mm)	Operating position		
JCL-TC 35W/830	37	88	0,42	3000K	3300	89	>79	>9000	G8.5	15 x 85	any		
JCL-TC 35W/942	37	88	0,42	4200K	3300	89	>88	>9000	G8.5	15 x 85	any		
JCL-TC 70W/830	72	83	0,87	3000K	6500	90	>81	>9000	G8.5	15 x 85	any		
JCL-TC 70W/942	72	83	0,87	4200K	5900	82	>88	>9000	G8.5	15 x 85	any		

Reference	Rated W	V	A	K	(Lm)	(Lm/W)	CRI (Ra)	Life (Hrs)	Base	Diameters (mm)	Operating position		
JCL-TD 70W/830	72	92	0,78	3000K	6500	90	>80	>9000	Rx7s	19 x 118	p45		
JCL-TD 70W/942	74	89	0,83	4200K	6000	81	>90	>9000	Rx7s	19 x 118	p45		
JCL-TD 150W/830	144	96	1,50	3000K	13250	92	>86	>9000	Rx7s	22 x 136	p45		
JCL-TD 150W/942	144	100	1,44	4200K	14200	99	>94	>9000	Rx7s	22 x 136	p45		

Reference	Rated W	V	A	K	(Lm)	(Lm/W)	Candela	CRI (Ra)	Life (Hrs)	angle	Base	Diameters (mm)	Operating position
JCL-R 20W/830 MR16 12D	20	100	0,20	3000K	1060	53	11000	>85	>8000	12°	GX10	51 x 66,5	any
JCL-R 20W/830 MR16 25D	20	100	0,20	3000K	1060	53	3500	>85	>8000	25°	GX10	51 x 66,5	any
JCL-R 20W/830 MR16 40D	20	100	0,20	3000K	1060	53	1700	>85	>8000	40°	GX10	51 x 66,5	any
JCL-R 20W/942 MR16 12D	20	100	0,20	4200K	1007	50	10450	>85	>8000	12°	GX10	51 x 66,5	any
JCL-R 20W/942 MR16 25D	20	100	0,20	4200K	1007	50	3325	>85	>8000	25°	GX10	51 x 66,5	any
JCL-R 20W/942 MR16 40D	20	100	0,20	4200K	1007	50	615	>85	>8000	40°	GX10	51 x 66,5	any
JCL-R 35W/830 MR16 12D	37	88	0,42	3000K	2100	57	16000	>88	>9000	12°	GX10	51 x 66,5	any
JCL-R 35W/830 MR16 25D	37	88	0,42	3000K	2100	57	5500	>88	>9000	25°	GX10	51 x 66,5	any
JCL-R 35W/830 MR16 40D	37	88	0,42	3000K	2100	57	3000	>88	>9000	40°	GX10	51 x 66,5	any
JCL-R 35W/942 MR16 12D	37	88	0,42	4200K	2100	57	16000	>88	>9000	12°	GX10	51 x 66,5	any
JCL-R 35W/942 MR16 25D	37	88	0,42	4200K	2100	57	5500	>88	>9000	25°	GX10	51 x 66,5	any
JCL-R 35W/942 MR16 40D	37	88	0,42	4200K	2100	57	3000	>88	>9000	40°	GX10	51 x 66,5	any

Reference	Rated W	V	A	K	(Lm)	(Lm/W)	Candela	CRI (Ra)	(Hrs)	angle	Base	Diameters (mm)	Operating position
JCL-R 35W/830 PAR20L 10D	37	88	0,42	3000K	2000	54	23000	>79	>6000	10°	E27	64 x 92	any
JCL-R 35W/830 PAR20L 30D	37	88	0,42	3000K	2000	54	5000	>79	>6000	30°	E27	64 x 92	any
JCL-R 35W/942 PAR20L 10D	37	88	0,42	4200K	1950	53	21500	>79	>7000	10°	E27	64 x 92	any
JCL-R 35W/942 PAR20L 30D	37	88	0,42	4200K	1950	53	5000	>79	>7000	30°	E27	64 x 92	any

Reference	Rated W	V	A	K	(Lm)	(Lm/W)	Candela	CRI (Ra)	Life (Hrs)	angle	Base	Diameters (mm)	Operating position
JCL-R 35W/830 PAR30L 10D	37	88	0,42	3000K	2200	59	44000	>79	>6000	10°	E27	64 x 92	any
JCL-R 35W/830 PAR30L 30D	37	88	0,42	3000K	2200	59	7400	>79	>6000	30°	E27	64 x 92	any
JCL-R 35W/942 PAR30L 10D	37	88	0,42	4200K	2090	56	41800	>79	>6000	10°	E27	64 x 92	any
JCL-R 35W/942 PAR30L 30D	37	88	0,42	4200K	2090	56	7030	>79	>6000	30°	E27	64 x 92	any
JCL-R 70W/830 PAR30L 10D	72	90	0,80	3000K	4850	67	68000	>91	>8000	10°	E27	64 x 92	any
JCL-R 70W/830 PAR30L 30D	72	90	0,80	3000K	4500	63	13500	>81	>8000	30°	E27	64 x 92	any
JCL-R 70W/830 PAR30L 40D	72	90	0,80	3000K	4850	67	10000	>81	>8000	40°	E27	64 x 92	any
JCL-R 70W/942 PAR30L 10D	72	90	0,80	4200K	4300	60	63000	>92	>7000	10°	E27	64 x 92	any
JCL-R 70W/942 PAR30L 30D	72	90	0,80	4200K	4300	60	13000	>92	>7000	30°	E27	64 x 92	any
JCL-R 70W/942 PAR30L 40D	72	90	0,80	4200K	4300	60	9000	>92	>7000	40°	E27	64 x 92	any

Reference	Rated W	V	A	K	(Lm)	(Lm/W)	Candela	CRI (Ra)	Life (Hrs)	angle	Base	Diameters (mm)	Operating position
JCL-R111 20W/830 10D	20	100	0,20	3000K	750	38	20000	>83	>8000	10°	GX8.5	111 x 95	any
JCL-R111 20W/830 24D	20	100	0,20	3000K	750	38	4500	>83	>6000	24°	GX8.5	111 x 95	any
JCL-R111 20W/942 10D	20	100	0,20	4200K	713	36	19000	>83	>8000	10°	GX8.5	111 x 95	any
JCL-R111 20W/942 24D	20	100	0,20	4200K	713	36	4275	>83	>6000	24°	GX8.5	111 x 95	any
JCL-R111 35W/830 10D	37	88	0,42	3000K	1100	30	35000	>79	>7000	10°	GX8.5	111 x 95	any
JCL-R111 35W/830 24D	37	88	0,42	3000K	1350	36	8500	>79	>7000	24°	GX8.5	111 x 95	any
JCL-R111 35W/830 40D	37	88	0,42	3000K	1350	36	4000	>79	>7000	40°	GX8.5	111 x 95	any
JCL-R111 35W/942 10D	37	88	0,42	4200K	1100	30	35000	>90	>7000	10°	GX8.5	111 x 95	any
JCL-R111 35W/942 24D	37	88	0,42	4200K	1350	36	8500	>90	>7000	24°	GX8.5	111 x 95	any
JCL-R111 35W/942 40D	37	88	0,42	4200K	1350	36	4000	>90	>7000	40°	GX8.5	111 x 95	any
JCL-R111 70W/830 10D	72	83	0,87	3000K	2500	35	50000	>82	>7000	10°	GX8.5	111 x 95	any
JCL-R111 70W/830 24D	72	83	0,87	3000K	2850	40	15000	>82	>7000	24°	GX8.5	111 x 95	any
JCL-R111 70W/830 40D	72	83	0,87	3000K	2850	40	9000	>82	>7000	40°	GX8.5	111 x 95	any
JCL-R111 70W/942 10D	72	83	0,87	4200K	2375	33	47500	>82	>7000	10°	GX8.5	111 x 95	any
JCL-R111 70W/942 24D	72	83	0,87	4200K	2850	40	15000	>93	>9000	24°	GX8.5	111 x 95	any
JCL-R111 70W/942 40D	72	83	0,87	4200K	2708	38	8500	>82	>7000	40°	GX8.5	111 x 95	any

www.jenbo.eu

